

[Home](#) > [Activities & Services](#) > [PatentScope](#) > [Patent Search](#)

[Home](#)

[About Patents](#)

[Patent Search](#)

[Content](#)

[Terms & Conditions](#)

[Glossary](#)

[Other Collections](#)

[PCT Resources](#)

[PCT Electronic Filing](#)

[Patent & Technical
Information](#)

[Statistics](#)

[Law of Patents](#)

[Meetings](#)

[E-mail Updates](#)

[Contact](#)

Related Links

[International Patent
Classification](#)

[Natural Language IPC
Search](#)

[Standards &
Documentation](#)

(WO/2002/061285) SCROLL COMPRESSOR

[Biblio. Data](#)

[Description](#)

[Claims](#)

[National Phase](#)

[Notices](#)

[Documents](#)

Latest bibliographic data on file with the International Bureau

Publication Number: WO/2002/061285 **International Application No.:** PCT/JP2002/061285
Publication Date: 08.08.2002 **International Filing Date:** 29.01.2002
Chapter 2 Demand Filed: 18.06.2002

Int. Class.: F04C 18/02 (2006.01), F04C 23/00 (2006.01), F04C 27/00 (2006.01), F04C 29/00 (2006.01)

Applicants: MATSUSHITA ELECTRIC INDUSTRIAL CO., LTD. [JP/JP]; 1006, Oaza K: 571-8501 (JP) (CN, JP, KR only).

IIDA, Noboru [JP/JP]; 6-18-8, Ichiriyama Otsu-shi, Shiga 520-2153 (JP) (U SAKUDA, Atsushi [JP/JP]; 2-7-11-405, Nojihigashi Kusatsu-shi, Shiga 525-0C HIWATA, Akira [JP/JP]; 2-7-11-219, Nojihigashi Kusatsu-shi, Shiga 525-0C SAWAI, Kiyoshi [JP/JP]; 1-13-2, Aoyama Otsu-shi, Shiga 520-2101 (JP) (I

Inventors: IIDA, Noboru [JP/JP]; 6-18-8, Ichiriyama Otsu-shi, Shiga 520-2153 (JP). SAKUDA, Atsushi [JP/JP]; 2-7-11-405, Nojihigashi Kusatsu-shi, Shiga 525-0C HIWATA, Akira [JP/JP]; 2-7-11-219, Nojihigashi Kusatsu-shi, Shiga 525-0C SAWAI, Kiyoshi [JP/JP]; 1-13-2, Aoyama Otsu-shi, Shiga 520-2101 (JP).

Agent: IWAHASHI, Fumio; c/o Matsushita Electric Industrial Co., Ltd. 1006, Oaza 571-8501 (JP).

Priority Data: 2001-19544 29.01.2001 JP

Title: SCROLL COMPRESSOR

Abstract: A scroll compressor that is easy of back pressure adjustment and capable of realizing high compression efficiency. The scroll compressor comprises a plurality of compression spaces formed by fixed spiral blades meshing with rotary spiral blades, a back pressure chamber disposed on the side opposite the rotary spiral blade surface of the rotary spiral member, high and medium pressure spaces obtained by partitioning the back pressure chamber by seal members, a first passageway for feeding lubricating oil, which is fed to the high pressure space, to the medium pressure space, a second passageway for feeding lubricating oil, which is fed to the medium pressure space, to the suction space of the compression space, wherein the first passageway is intermittently put in communication by the rotary movement of a rotary spiral member.

Designated States: CN, JP, KR, US.

Publication Language: Japanese (JA)

Filing Language: Japanese (JA)

[[Printable version](#)]